



Schäfer + Peters GmbH
Competence in Stainless Steel



FEATURES:

- ✓ 60° Decorative head
- ✓ cutting point
- ✓ Stripping ribs
- ✓ ribs under the head
- ✓ TX driving feature
- ✓ Special smooth coating

ETA - 11/0283



DOUBLE RAISED COUNTERSUNK HEAD TIMBER SCREWS
WITH RIPS AND CUTTING POINT
ARTICLE 9242 1.4006 TX



ARTICLE 9242 1.4006 TX DOUBLE RAISED COUNTERSUNK HEAD TIMBER SCREWS WITH RIPS AND CUTTING POINT

USES:

Ideal for all companies involved in wood processing (carpenters, timber construction) and all horticulturists and landscapers for fastening timbers and landing stages. Also the ideal solution for hardwoods such as Bankirai, Massaranduba, and many more.

A minimum screw-in depth of 4 x the diameter must be ensured. A screw-in depth of 8 x the diameter should be achieved depending on the wood.

FEATURES:

- 60° Decorative head
- cutting point
- Stripping ribs
- ribs under the head
- TX driving feature
- Martensitic stainless steel hardened (1.4006)
- Special smooth coating

BENEFITS:

Stripping ribs
The stripping ribs ensure low screw-in torques even with high attachment parts

No predrilling

Predrilling is not needed in most cases. We do however always recommend testing the application.

Wobble-free driving feature

The TX inner multi-tooth drive allows the screw to be easily and securely screwed in when the screw is attached and countersunk.

Timber is not torn out

The Cut tip ensures accurate attachment on hardwood without tearing out.



Schäfer + Peters GmbH
Zeilbaumweg 32
DE-74613 Öhringen

Tel. +49 (0) 7941 6094-0
Fax +49 (0) 7941 6094-700

info@schaefer-peters.com
www.schaefer-peters.com

d d	l l	b b	dk dk	k k	Antrieb Drive size	Artikelnummer Item Number	
4	30	18	6	2,75	TX15	9242400640 30/18	200
	35	24	6	2,75	TX15	9242400640 35/24	200
	40	24	6	2,75	TX15	9242400640 40/24	200
	45	30	6	2,75	TX15	9242400640 45/30	200
	50	30	6	2,75	TX15	9242400640 50/30	200
	60	36	6	2,75	TX15	9242400640 60/36	200
4,5	40	24	7	3,35	TX20	9242400645 40/24	200
	45	30	7	3,35	TX20	9242400645 45/30	200
	50	30	7	3,35	TX20	9242400645 50/30	200
	60	36	7	3,35	TX20	9242400645 60/36	200
	70	42	7	3,35	TX20	9242400645 70/42	200
	80	48	7	3,35	TX20	9242400645 80/48	200
5	40	24	7,5	3,45	TX25	9242400650 40/24	200
	45	30	7,5	3,45	TX25	9242400650 45/30	200
	50	30	7,5	3,45	TX25	9242400650 50/30	200
	60	36	7,5	3,45	TX25	9242400650 60/36	200
	70	42	7,5	3,45	TX25	9242400650 70/42	200
	80	48	7,5	3,45	TX25	9242400650 80/48	200
	90	54	7,5	3,45	TX25	9242400650 90/54	200
	100	60	7,5	3,45	TX25	9242400650 100/60	200

